



PlumbMaster, Inc.

NEW PRODUCT

NEOPERL®

1.0 GPM WATER SAVING FAUCET ATTACHMENTS

- Pressure Compensating 1.0 GPM for Constant Flow from 20 to 80 PSI
- Provides Non-Splashing, Non-Aerated Spray
- Anti-Clogging Dome Screen Filters Sediment and Particles
- Color-Coded to Identify Flow Rate
- Virtually Unbreakable Single Piece Insert Ensures a Longer Usable Life



- Cat. No. 36150 Regular Male 15/16"
- Cat. No. 36150T Regular Male 15/16" (Tube of 6)
- Cat. No. 36153 Regular Male 15/16" (Vandal Proof)
- Cat. No. 36151 Regular Female 55/64"
- Cat. No. 36151T Regular Female 55/64" (Tube of 6)
- Cat. No. 36154 Regular Female 55/64" (Vandal Proof)
- Cat. No. 36152 Regular Dual Thread 15/16" x 55/64"
- Cat. No. 36152T Regular Dual Thread 15/16" x 55/64" (Tube of 6)
- Cat. No. 36155 Regular Dual Thread 15/16" x 55/64" (Vandal Proof)
- Cat. No. 36156 Jr Male 13/16"
- Cat. No. 36157 Jr Female 3/4"

