

WOLVERINE BRASS, INC.


FINALE TWIN HANDLE LAVATORY FAUCET

LESS POP-UP

- FC00350 - CHROME / LEVER HANDLES
- FC00450 - BRUSH NICKEL / LEVER HANDLES
- FC00340 - CHROME / CANOPY WRISTBLADE HANDLES

WITH POP-UP

- FC01350 - CHROME / LEVER HANDLES
- FC01450 - BRUSH NICKEL / LEVER HANDLES
- FC01340 - CHROME / CANOPY WRISTBLADE HANDLES



LEVER
HANDLE

FAUCET CONSTRUCTION:

- CERAMIC DISK CARTRIDGES.
- HEAVY CAST BRASS BODY WITH INTEGRAL SHANKS.
- 1/2" IPS THREADED BRASS SHANKS 4" ON CENTERS.
- SOLID BRASS POP-UP.

OPERATION:

- TWIN LEVER OR CANOPY WRIST BLADE HANDLE.
- REQUIRES LESS THAN 5 LB FORCE TO OPERATE.
- TEMP. ADJUSTMENT 90° FROM FULL OFF TO FULL ON.
- 1.2 GPM (4.5 L/min) AERATOR.

STANDARDS:

- LOW LEAD COMPLIANT (0.25% Pb MAX).
- DESIGNED AND MANUFACTURED TO COMPLY WITH CSA B-125 ASME A112.18.1M, NSF AND ADA STANDARDS.

MOUNTING SURFACE REQUIREMENTS:

- SURFACE THICKNESS 1-1/4" MAXIMUM.
- LESS POP-UP - TWO (7/8" MIN TO 1-1/4" MAX DIA.) HOLES 4" ON CENTERS.
- WITH POP-UP - THREE (7/8" MIN TO 1-1/4" MAX DIA.) HOLES 2" ON CENTERS.



CANOPY
WRIST BLADE
HANDLE

