




ETERNTIY® BY WOLVERINE BRASS

TWO HANDLE 4" DECK MOUNT DOUBLE SERVICE FIXTURE WITH 8" SPREAD SWING SPOUT


FAUCET CONSTRUCTION:

- CERAMIC DISC CARTRIDGES.
- CHROME PLATED MACHINED BRASS BODY.
- CHROME PLATED HEAVY RED BRASS SPOUT WITH 1.8GPM AERATOR.
- CHROME PLATED METAL 4" WRIST BLADE HANDLES OR CHROME PLATED SOLID BRASS CROSS HANDLES..
- BRASS SUPPLY CONNECTIONS WITH 1/2"IPS THREADS.

9333157
WRISTBLADE
HANDLES



9333557
CROSS
HANDLES



OPERATION:

- TWIN 4" WRIST BLADE HANDLES OR CROSS HANDLES.
- HANDLES REQUIRES LESS THAN 5 LB FORCE TO OPERATE VALVE.
- 90° TURN FROM FULL OFF TO FULL ON.

STANDARDS:

- LOW LEAD COMPLIANT (0.25% Pb MAX)
- DESIGNED AND MANUFACTURED TO COMPLY WITH CSA B-125, ASME A112.18.1M AND NSF STANDARDS.

MOUNTING SURFACE REQUIREMENTS:

- SURFACE THICKNESS 1" MAXIMUM.
- TWO 7/8" DIA. MINIMUM HOLES 4" ON CENTER.

WRISTBLADE HANDLES

CROSS HANDLES

